# C. If the Settlement Is Denied, Grant of KFLY's Upgrade Application Would Better Serve The Public Interest

With the allotment of Channel \*268C3 at The Dalles no longer in consideration, the Commission (if it continues to refuse approval of the MBI/American Radio settlement) is faced with a conflict between the KFLY upgrade and the KBBT-FM upgrade. Data already before the Commission demonstrates the KFLY upgrade would better serve the public interest. By upgrading KBBT-FM to Class C1 status, the station would serve an additional area of 7,908 square kilometers with a population of 221,322 persons. But KFLY operating as a Class C station would serve an additional area of 9,490 square kilometers and an additional population of 325,969 persons --104,647 more persons than KBBT-FM.<sup>15</sup> The fact that KFLY's upgrade would provide service to a substantially larger area and substantially larger number of persons should be dispositive. Yet, even if it were not, other factors favor the KFLY proposal. KFLY is only one of two commercial FM stations licensed to Corvallis, which has a population of 46,244. Indeed, there are only two FM commercial allotments in Benton County, in which Corvallis is situated. Conversely, KBBT-FM is situated in the Portland, Oregon metropolitan market -- the nation's 24th largest radio market. Duncan's Radio Market Guide (1998 Ed.). Indeed, according to an engineering statement filed in this proceeding, the additional area that would be served as the result of KBBT-FM's upgrade is within the primary service contour of 44 other stations. Comments of Hurricane Broadcasting, Engineering Statement, Table A (filed March 28, 1996).

Exhibit 1 of Consolidated Joint Counterproposal Reply Comments, filed July 3, 1996 by Common Ground Broadcasting, Inc. and Combined Communications, Inc.

MBI has shown that Channel \*268C3 at The Dalles should not be considered in this proceeding. However, if that allotment were considered, MBI's proposal for KFLY still should prevail. Significantly, The Dalles, with a population of 11,060 persons (approximately one fourth that of Corvallis), already receives local service from three FM stations and AM stations. The combined population that would receive new service from the KBBT-FM upgrade and the new allotment on Channel \*268C3 at The Dalles would still be more than 45,000 persons smaller than the population gaining new service from KFLY's proposed Class C facilities. The R&O based its preference for The Dalles/KBBT-FM combination on the grounds that The Dalles proposal would provide that community with its first noncommercial educational service. The R&O, however, does not cite any case in which a first noncommercial educational service to a well served community was found to be a prevailing factor over other "public interest considerations," such as new service to a substantially larger population.

In <u>Revision of FM Assignment Policies and Procedures</u>, 90 FCC 2d 88, 92 n. 8 (1982), the Commission enumerates some of the factors that may be taken into consideration under the "other public interest matters" criterion: "the number of aural services received in the proposed service area, the number of local services, the need for or lack of public radio service and other matters such as the relative size of the proposed communities and their growth rate." These "other factors" are not ranked in order of importance. Thus, the establishment of a noncommercial educational service is not <u>ipso facto</u>, more important than providing new service to a larger number of persons. In this case, the fact a substantially greater population that would receive new service from KFLY's Class

C upgrade is more significant than the addition of a sixth local service, albeit the first noncommercial educational service, to a community one-fourth the size of Corvallis.

### IV. SUMMARY

On reconsideration, the Commission's staff is urged to approve the settlement agreement proffered in good faith by MBI and American Radio. In doing so, the conflicts between those parties will be at an end and expanded service can quickly be provided by both American Radio's KBBT-FM and MBI's KFLY. If the Commission declines to approve the settlement, it must chose between the KFLY upgrade and the conflicting proposals before it. As an initial matter, the proposed allotment of Channel \*268C3 to The Dalles does not come into play. Any one of the five reasons outlined above should not be made and should not be considered herein. Faced with the comparison between the KFLY upgrade and the KBBT upgrade, the KFLY upgrade must be preferred.

WHEREFORE, in light of all circumstances present, Madgekal Broadcasting, Inc. herein respectfully requests that the Commission reconsider the Report and Order in the above-captioned proceeding and grant the relief requested herein.

GEKAL BROADCASTING INC.

Matthew H. McCormick

Its Counsel

Reddy, Begley & McCormick 2175 K Street, N.W., Suite 350 Washington, D.C. 20037 (202) 659-5700

May 19, 1998

MBI notes that on May 15, 1998, it tendered a one-step upgrade application for KFLY specifying Class C1 facilities at the same site identified in BPH-960206IF. In an accompanying transmittal letter, MBI stated that the modification application was being submitted as an interim measure because final resolution of this proceeding may take a substantial amount of time. MBI requested, to the extent necessary, waiver of Section 73.3517 and Section 73.3518 of the Rules.

### **EXHIBIT A**

## McCLANATHAN REPORT

FOR MADGEKAL BROADCASTING, INC.
CONCERNING AVAILABILITY OF NCE AND COMMERCIAL
FM CHANNELS TO SERVE THE DALLES, OREGON

### MCCLANATHAN AND ASSOCIATES, INC.

PROFESSIONAL ELECTRICAL ENGINEERS
P.O. BOX 939 - PORTLAND, OREGON 97207-0939
TEL: (503) 246-8080 FAX: (503) 246-6304

#### ENGINEERING REPORT

for

### MADGEKAL BROADCASTING, INC.

concerning

## AVAILABILITY OF NCE AND COMMERCIAL FM CHANNELS TO SERVE THE DALLES, OREGON

#### INTRODUCTION

McClanathan and Associates, Inc., Professional Electrical Engineers, has been retained by Madgekal Broadcasting, Inc. to determine if there is a NCE reserved FM channel available to serve The Dalles, Oregon and to comment on the allocation of FM channel \*268C3 to The Dalles in lieu of channel \*256C3.

### THE DALLES TOPOGRAPHY

FM radio service to The Dalles, Oregon has particular problems due to the geographic topographic features of the area. Exhibit 1 is a portion of The Dalles South 7.5 minute USGS topographic quadrangle map showing the incorporated city of The Dalles along the South shore of the Columbia River which separates the States of Oregon and Washington. The Columbia River flows to the West through a deep gorge carved out during the last glacial period.

The city of The Dalles is surrounded by hills on the Southeast, South and Southwest. The greatest portion of The Dalles, including all of the business and industrial areas, are located in low elevations near the river in an area shaped somewhat like the bottom of a bowl. The elevation of the Columbia River is typically 72 feet AMSL and the center of The Dalles is 240 feet AMSL. The hills on the North shore, across the river from The Dalles, have elevations typically between 1200 and 3100 feet AMSL. For convenience, elevations and distances will be stated in British measurement units of feet and miles since the attached map exhibits show elevations only in feet.

#### EXISTING ANTENNA SITES

Nearly all VHF and UHF communications, FM radio and TV broadcasting antenna sites are located on the ridge of hills across the river and approximately 14 km (8.7 miles) to the North of The Dalles. A typical established antenna site is

Stacker Butte with an elevation of 3220 feet AMSL. The Stacker Butte location provides the optimum and complete line-of-sight radio propagation to 100 percent of all areas of The Dalles.

Another existing radio communications site on Haystack Butte is also located North of the Columbia River and East of The Dalles and Stacker Butte. Although this site if further to the East it does provide line-of-sight propagation to nearly all of The Dalles.

### NCE FM CHANNEL STUDY

A FM channel interference study was done to determine if there are any reserved NCE FM channels available to serve The Dalles. For this study an existing communications site near Stacker Butte was used. This site is the location of FM translator station K256AC and numerous TV translator services. K256AC operates with 0.01 kW ERP and provides excellent coverage into all of The Dalles from this site.

The results of this study is attached as Exhibit 2 which demonstrates that NCE channels 201, 211, 213 and 215 have possibility for use at this site. An antenna power of 0.20 kW ERP was used which is a class C3 station at the Stacker Butte antenna HAAT of 561 meters.

The nearest channel 6 TV station is KOIN TV in Portland, Oregon which is an affected station. A study was done for channel 215C3 using the Dataworld, Inc. computer services to determine the total population within the calculated KOIN TV predicted interference area. Exhibit 3 shows, for channel 215 operating as a class C3 station from Stacker Butte, the total interference area to KOIN TV is 70.6 square kilometers and the population within this interference area is 497 persons. Since this is less than 3000 persons it is possible to use NCE channel 215 to serve The Dalles with a class C3 NCE station.

#### ALLOCATION OF CHANNEL \*268C3 TO THE DALLES

On November 20, 1995 LifeTalk Broadcasting Association (Lifetalk), erroneously stating that no NCE FM channel was available to serve The Dalles, petitioned the FCC to allocate FM channel 256C3 to The Dalles and reserve it for NCE applicants. On February 13, 1996 the FCC released a Notice of Proposed Rule Making, MM Docket No. 96-12, RM-8741, (PRM) proposing to allocate FM channel \*268C3 to The Dalles. The FCC stated, in footnote 1. of this PRM, that "The staff engineering analysis of Channel 256C3 shows that the closest unobstructed transmitter site is 22.8 kilometers from The Dalles, which results in only half the community being covered with a 70 dBu city-grade signal." The FCC proposed instead to allocate channel \*268C3 to The Dalles but with a site restriction of 8.8 km to the Southwest to avoid short-spacing to Station KPLZ, channel 268C in Seattle, Washington.

Notwithstanding the engineering analysis performed by the FCC staff, a brief examination of the area surrounding The Dalles conclusively demonstrates that channel 268C3 can not provide adequate line-of-sight coverage to the community of The Dalles from any possible antenna location in compliance with 47 C.F.R. Section 73.315(b). Additionally, the channel 256C3 originally requested by Lifetalk, can indeed provide line-of-sight and 70 dBu coverage to The Dalles.

The problem for channel 268C3 is that any antenna site must be located to the South of The Dalles to avoid short-spacing to Station KPLZ, channel 268C in Seattle, Washington as described in the FCC PRM. Since the community of The Dalles is surrounded by high ridges of the Columbia River Gorge to the East, South and West any possible antenna site will suffer terrain obstructions into The Dalles city area. This terrain obstruction is so severe that even a very tall antenna support structure will not overcome the topographic shielding.

Four, 7.5 minute USGS topographic maps are attached for convenience in reviewing the terrain obstructions. Exhibit 5 is a copy of the Wishram quadrangle. Marked on Exhibit 5 is a location on Haystack Butte with an elevation of 2846 feet AMSL at geographic coordinates 45-41-01N and 120-57-17W.

A channel 256C3 FM channel spacing study was obtained for this location on Haystack Butte and is attached as Exhibit 4. This study demonstrates this channel may be allocated to The Dalles in compliance with 47 C.F.R. Section 73.207(b)(1). A class C3 station from this Haystack Butte location will provide all of The Dalles with 70 dBu signal coverage as shown on the contour map, Exhibit 11. Attached to Exhibit 11 is a tabulation of the terrain and coverage data for this transmitter location.

Exhibit 6 is a copy of the Emerson quadrangle. Marked on Exhibit 6 is the location of the "global coordinates" suggested as a transmitter location for channel 268C3. This site, on the ridge above and West of the Deschutes River, has an elevation of 1245 feet AMSL at geographic coordinates 45-34-00N and 120-55-00W.

Exhibit 7 is a copy of the Petersburg quadrangle and marked on this map is the location at "Japanese Hollow" with an elevation of 918 feet AMSL at geographic coordinates 45-31-28N and 121-07-22W. These are the FCC site coordinates specified by the FCC in footnote 3. of the February 13, 1996, MM Docket No. 96-12, RM-8741 PRM, as necessary to provide the required 237 km spacing to co-channel Station 268C KPLZ in Seattle.

Exhibit 1A is a copy of The Dalles South quadrangle map which shows elevations above MSL of the hills surrounding The Dalles to the South.

#### TERRAIN SHIELDING

A study was completed to demonstrate the effect of terrain shielding to the city of The Dalles from the three FM antenna sites. These locations are the "global coordinates" and "FCC coordinates" sites specified for channel \*268C3 and "Haystack Butte" suggested for the channel 256C3 antenna site.

Radial profile graphs were prepared from the three sites to show the elevation topography of the intervening land between the antenna site and the city of The Dalles. The official May 1998 corporate city limit boundary for The Dalles was obtained from the city planning office. This city boundary is shown in Exhibit 1.

The elevations obtained for the radial profile graphs were obtained from NGDC 3 second Digital Elevation Models and, when compared to the elevations on the 7.5 minute topographic maps Exhibits 5-8, compare quite closely with sufficient accuracy.

Six equally spaced radial profile graphs were drawn from the "global coordinates" site over the city of The Dalles as shown in Exhibit 8. The Dalles corporate boundaries are marked on each profile graph. A line-of-sight line is drawn on each graph from a proposed transmitting antenna center of radiation located at an elevation of 213 meters (700 feet) AGL, 593 (1945 feet) MSL.

It is obvious from the profile graphs that nearly all of The Dalles is severely shadowed from the antenna site by terrain obstructions. Only the small most Northwest area of The Dalles will receive line-of-sight coverage as shown on the N284E degree radial, page 5 of Exhibit 8. Moreover, it is easily demonstrated by simple geometry using a straight edge that, even if the transmitting antenna height were increased to 474 meters (1555 feet) AGL or 2800 feet MSL, less than one-half of The Dalles would receive line-of-sight signal propagation.

A similar radial profile study was conducted for the "FCC coordinates" location near Japanese Hollow as shown in Exhibit 9. A 700 foot high tower was used to draw the line-of-sight propagation from the antenna to the terrain obstruction. Eight profile graphs were prepared with equal spacing to cover the city of The Dalles. The radial profile graphs demonstrate that this "FCC coordinates" site can not provide line-of-sight signal propagation to The Dalles because of significant terrain obstructions. It is most unlikely that any applicant for such an allocation would be able to construct a 700 foot high antenna supporting structure.

Community Development Department, City of The Dalles, 313 Court Street, The Dalles, OR 97058, Tel: 541-296-5481.

The third antenna site studied is the "Haystack Butte" site that is suitable for use with channel 256C3. Exhibit 10 consists of 10 profile graphs prepared with equal spacing to cover the city of The Dalles. An antenna height of only 25.6 meters (84 feet) AGL was used to prepare the line-of-sight propagation to obstructions and the city of The Dalles.

The profile graphs demonstrate that the "Haystack Butte" site does provide line-of-sight signal propagation to most of the city of The Dalles with a few local hills causing minor shielding within the city. A modest transmitting antenna height increase would eliminate nearly all of these minor shadow areas.

#### CONCLUSIONS

The optimum FM channel for serving The Dalles with non-commercial educational programming is NCE channel 215. The preferred transmitter and antenna site is Stacker Butte directly across the Columbia River from The Dalles. This site provides line-of-sight signal propagation to 100 percent of the city of The Dalles with a very low transmitting antenna height AGL. A class A or minimum power class C3 facility may be located at Stacker Butte and not cause prohibited interference to the channel 6 TV station KOIN in Portland.

The FCC allocation of channel 268C3 to The Dalles is unsuitable because of the required site restriction to the South of The Dalles to provide the 237 km minimum distance separation requirement to Station KPLZ, channel 268C in Seattle, Washington. Because of severe terrain obstructions there is no possible antenna allocation location for channel 268C3, even with an absurdly high tower, that will provide line-of-sight signal propagation into The Dalles.

Allocation of channel 256C3 to The Dalles will enable the cities of The Dalles, Oregon and Goldendale, Washington to be totally covered with a 70 dBu city-grade signal. A site restriction of 20 km (12.4 miles) to the East, using the "Haystack Butte" geographic coordinates of 45-41-01N, 120-57-17W, is required to avoid a short-spacing to Station KODZ, channel 256C, Eugene, Oregon. The "Haystack Butte" site is served with electrical power and line-of-sight signal propagation to nearly all of the city of The Dalles is possible with a very short antenna supporting structure. The high antenna HAAT at this site limits the maximum class C3 antenna power at this site to approximately 0.80 kW ERP.

It is suspected the FCC staff engineering analysis as reported in the PRM, which favored channel 268C3 in lieu of channel 256C3 at The Dalles, was faulted because of a lack of staff access to either the 7.5 minute USGS topographic quadrangle maps or 30 meter USGS computer topographic data for the area.

## Engineering report prepared by:





Robert A. McClanathan, P.E. McClanathan and Associates, Inc. P.O. Box 939
Portland, Oregon 97207

May 11, 1998

STATE OF OREGON

SS:

County of Multnomah)


ROBERT A. McCLANATHAN, being duly sworn upon oath, deposes and says:

- 1. That he is President of McClanathan and Associates, Inc., Professional Electrical Engineers.
- 2. That he is a licensed Professional Electrical Engineer in the States of California, Oregon, Washington and the District of Columbia, that he is a member of the Association of Federal Communications Consulting Engineers and that he is a licensed radio operator holding FCC License Number PG-13-13526.
- 3. That he has been engaged in governmental, educational, commercial radio and television broadcast engineering and developments since 1955.
- 4. That he has been retained by Madgekal Broadcasting, Inc. to prepare the engineering exhibits to demonstrate the availability of certain FM broadcast channels to serve The Dalles, Oregon.

Affiant finally states that the material and exhibits contained in this report were prepared by him or under his direct supervision and that he has checked all results and believes them to be true.


Robert A. McClanathan, P.E.


Subscribed and sworn to before me this 11th day of May, 1998.



Notary Public, Oregon

In and for the County of Multnomah, State of Oregon.





## EXHIBIT 2

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 41 May 5, 1998

### FM Interference study

Title: THE DALLES, OR Channel 201C2 ( 88.1 MHz) ERP: .20 kW; EAH: 561 m Database: FCC 04/09/98  Latitude: 45-42-43 Longitude: 121-07-00 Safety zone: 80 km
Call Auth Licensee name Chan ERP-kW Latitude Br-to Dist. Req. City of License St FCC File no. Freq EAH-m Longitude -from (km) (km)
KOIN LIC KOIN-TV, INC. 6 100 45-30-58 260.8 127.9 186.3 PORTLAND OR 85.0 533 122-43-59 79.6 -58.4 SHORT Proposed F(50,10) 48 dBu = 63.13 km; KOIN F(50,50) 47 dBu = 123.2 km
KSFH APC St Francis High Sch. of *200D .010 37-22-08 185.3 930.1 49.07 Mountain View CA 87.9 -74 122-05-02 4.6 881.0 CLEAR Proposed F(50,10) 54 dBu = 45.89 km; KSFH F(50,50) 60 dBu = 3.179 km Proposed F(50,50) 60 dBu = 29.40 km; KSFH F(50,50) 54 dBu = 4.529 km
KAYB       CP       American Family Associat *201A       .25       46-19-53       50.6       109.7       94.08         Sunnyside       WA       88.1       -57       120-00-51       231.4       15.60       CLOSE         Proposed F(50,10)       40 dBu = 86.89 km; KAYB       F(50,50)       60 dBu = 7.191 km         Proposed F(50,50)       60 dBu = 29.40 km; KAYB       F(50,10)       40 dBu = 23.93 km
KLRO CP LifeTalk Broadcasting As *201A .20 46-48-36 7.6 123.2 93.67  Nile WA 88.1 -33 120-54-10 187.7 29.49 CLEAR  Proposed F(50,10) 40 dBu = 86.89 km; KLRO F(50,50) 60 dBu = 6.781 km  Proposed F(50,50) 60 dBu = 29.40 km; KLRO F(50,10) 40 dBu = 22.58 km
NEW CP Trustees of Central Wash *201A .50 47-00-21 17.6 151.1 95.47 Ellensburg WA 88.1 -58 120-30-55 198.0 55.62 CLEAR Proposed F(50,10) 40 dBu = 86.89 km; NEW F(50,50) 60 dBu = 8.578 km Proposed F(50,50) 60 dBu = 29.40 km; NEW F(50,10) 40 dBu = 28.75 km
KTCV LIC Kennewick School Distric *201A .32 46-13-05 68.5 158.5 94.53 Kennewick WA 88.1 -27 119-12-17 249.8 63.99 CLEAR Proposed F(50,10) 40 dBu = 86.89 km; KTCV F(50,50) 60 dBu = 7.645 km Proposed F(50,50) 60 dBu = 29.40 km; KTCV F(50,10) 40 dBu = 25.51 km
NEW APC Lane Community College *201A .45 44-04-40 185.4 182.4 106.2 Bend OR 88.1 160 121-19-49 5.2 76.21 CLEAR Proposed F(50,10) 40 dBu = 86.89 km; NEW F(50,50) 60 dBu = 19.29 km Proposed F(50,50) 60 dBu = 29.40 km; NEW F(50,10) 40 dBu = 59.96 km
NEW       APC       CSN International       *201A       2.15       44-04-40       185.4       182.4       115.0         Bend       OR       88.1       166       121-19-49       5.2       67.41       CLEAR         Proposed F(50,10)       40 dBu = 86.89 km; NEW       F(50,50)       60 dBu = 28.09 km         Proposed F(50,50)       60 dBu = 29.40 km; NEW       F(50,10)       40 dBu = 81.49 km
KBVM       LIC       Metro       Catholic       Broadcast       *202C2       1.90       45-30-58       260.8       127.9       93.83         Portland       OR       88.3       428BT122-43-59       79.6       34.12       CLEAR         Proposed F(50,10)       54 dBu = 45.89 km; KBVM       F(50,50)       60 dBu = 42.46 km         Proposed F(50,50)       60 dBu = 29.40 km; KBVM       F(50,10)       54 dBu = 64.43 km
KYSC       LIC       Yakima       School District N *203A       3 46-35-06 24.8 107.2 33.65         Yakima       WA       88.5 -77 120-31-41 205.2 73.52 CLEAR         Proposed F(50,50)       80 dBu = 7.717 km; KYSC       F(50,50) 60 dBu = 13.33 km         Proposed F(50,50)       60 dBu = 29.40 km; KYSC       F(50,50) 80 dBu = 4.247 km

## MCCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 42 May 5, 1998

## FM Interference study

Title: THE DALLES, OR Channel 201C2 ( 88.1 MHz) ERP: .20 kW; EAH: 561 m  Latitude: 45-42-43 Longitude: 121-07-00									
Call Auth Licensee name Chan ERP-kW Latitude Br-to Dist. Req. City of License St FCC File no. Freq EAH-m Longitude -from (km) (km)									
KLVP-FM APC Educational Media Founda *204C1 3.70 45-20-01 228.0 62.73 55.23 Cherryville OR 88.7 532 121-42-45 47.6 7.505 CLOSE Cut-off 08/28/97 Proposed F(50,50) 100 dBu = .978 km; KLVP-FM F(50,50) 60 dBu = 54.25 km									
Proposed F(50,50) 60 dBu = 29.40 km; KLVP-FM F(50,50) 100 dBu = 3.894 km  KLVP-FM LIC Educational Media Founda *204A .22 45-19-57 228.1 63.01 30.42  Cherryville OR 88.7 478 121-42-57 47.7 32.58 CLEAR  Proposed F(50,50) 100 dBu = .978 km; KLVP-FM F(50,50) 60 dBu = 27.37 km  Proposed F(50,50) 60 dBu = 29.40 km; KLVP-FM F(50,50) 100 dBu = 1.026 km									
KLES LIC First Love Ministries, I 254A 1.50 46-07-36 61.4 97.90 15 Mabton WA BLH-971202KE 98.7 195 120-00-12 242.2 82.90 CLEAR									
<pre>KWJZ LIC Roy H. Park Broadcasting 255C 58DA 47-30-14 342.1 209.8 35 Seattle</pre>									

>> End of channel 201C2 study <<

## FM Interference study

Title: THE DALLES, OR Channel 211C2 ( 90.1 MHz) ERP: .20 kW; EAH: 561 m Database: FCC 04/09/98  Latitude: 45-4 Longitude: 121-6 Safety zone:	07-00
Call Auth Licensee name Chan ERP-kW Latitude Br-to Dist. City of License St FCC File no. Freq EAH-m Longitude -from (km)	Req.
KOIN LIC KOIN-TV, INC. 6 100 45-30-58 260.8 127.9  PORTLAND OR 85.0 533 122-43-59 79.6 -15.3  Proposed F(50,10) 67.4 dBu = 20.01 km; KOIN F(50,50) 47 dBu = 123.	143.2 SHORT
NEW       APC       Positive Programming Fou *208C3       .58       45-20-01 228.0 62.73         Pine Grove       OR       89.5       529 121-42-45 47.6 24.82         Proposed F(50,50)       100 dBu = .978 km; NEW       F(50,50) 60 dBu = 36.9         Proposed F(50,50)       60 dBu = 29.40 km; NEW       F(50,50) 100 dBu = 1.55	CLEAR 3 km
NEW APC Educational Media Founda *208C1 5.20DA 45-20-01 228.0 62.73  Pine Grove OR 89.5 540 121-42-45 47.6 3.663  Cut-off 07/25/97; DA: oddball ODD970318MA @ 0 deg  Proposed F(50,50) 100 dBu = .978 km; NEW F(50,50) 60 dBu = 58.0	CLOSE
Proposed F(50,50) 100 dBu = .978 km; NEW F(50,50) 60 dBu = 58.0 Proposed F(50,50) 60 dBu = 29.40 km; NEW F(50,50) 100 dBu = 4.49  ALLOC *208C1 46-31-42 26.6 101.8	73.28
Wapato WA 89.5 120-31-16 207.0 28.47 Proposed F(50,50) 100 dBu = .978 km; ALLOC F(50,50) 60 dBu = 72.3 Proposed F(50,50) 60 dBu = 29.40 km; ALLOC F(50,50) 100 dBu = 10.1	CLEAR 1 km
KSOH LIC Central Washington Educa *208C2 9.50 46-31-42 26.6 101.8 Wapato WA 89.5 297 120-31-16 207.0 51.36 Proposed F(50,50) 100 dBu = .978 km; KSOH F(50,50) 60 dBu = 49.4 Proposed F(50,50) 60 dBu = 29.40 km; KSOH F(50,50) 100 dBu = 4.86	CLEAR 1 km
<pre>KWFJ LIC Calvary Baptist Church *209A 1DA 46-57-59 322.3 177.8 Roy WA 89.7 30 122-32-56 141.2 145.2 DA: oddball ODD911210ME @ 0 deg</pre>	
Proposed $F(50,50)$ 80 dBu = 7.717 km; KWFJ $F(50,50)$ 60 dBu = 10.2 Proposed $F(50,50)$ 60 dBu = 29.40 km; KWFJ $F(50,50)$ 80 dBu = 3.17	25 km 79 km
KBPS-FM LIC       Benson Polytechnic Schoo *210C2 8.70       45-30-58 260.8 127.9         Portland       OR       89.9 293 122-43-59 79.6 27.16         Proposed F(50,10)       54 dBu = 45.89 km; KBPS-FM F(50,50) 60 dBu = 48.3         Proposed F(50,50)       60 dBu = 29.40 km; KBPS-FM F(50,10) 54 dBu = 71.3	CLEAR 33 km
KOLU LIC Riverview Baptist Christ *211C2 4.10 46-04-59 74.0 157.3 Pasco WA 90.1 305 119-09-38 255.5 21.92 Proposed F(50,10) 40 dBu = 86.89 km; KOLU F(50,50) 60 dBu = 42.5 Proposed F(50,50) 60 dBu = 29.40 km; KOLU F(50,10) 40 dBu = 106.80 km; KOLU F(50,10) 40 dBu = 106.80 km; KOLU F(50,10)	CLEAR 58 km
KNWY LIC Washington State Univers *212C3 1.90 46-31-57 26.9 102.5 Yakima WA 90.3 273 120-30-37 207.3 21.17 Proposed F(50,10) 54 dBu = 45.89 km; KNWY F(50,50) 60 dBu = 34.6 Proposed F(50,50) 60 dBu = 29.40 km; KNWY F(50,10) 54 dBu = 51.9	CLEAR 67 km

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 62 May 5, 1998

## FM Interference study

Title: THE DALLES, OR Channel 211C2 ( 90.1 MHz) ERP: .20 kW; EAH: 561 m  Latitude: 45-42-43 Longitude: 121-07-00									
Call Auth Licensee name Chan City of License St FCC File no. Freq	ERP-kW Latitude Br-to Dist. Req. EAH-m Longitude -from (km) (km)								
KZOELICColumbia Heights Christi *212ALongviewWA90.Proposed F(50,10)54 dBu = 45.89 km; KZOProposed F(50,50)60 dBu = 29.40 km; KZO	3 239 122-51-14 109.8 74.00 CLEAR E $F(50,50)$ 60 dBu = 23.86 km								
NEW       APC       The Commun. Advisory Bd. *213A         Bend       OR       90.         Proposed F(50,50)       80 dBu = 7.717 km; NEW         Proposed F(50,50)       60 dBu = 29.40 km; NEW	5 177 121-19-57 5.3 146.9 CLEAR $F(50,50)$ 60 dBu = 19.70 km								
KBOO       LIC       The KBOO Foundation       *214C         Portland       OR       90.         Proposed F(50,50)       100 dBu = .978 km; KBO         Proposed F(50,50)       60 dBu = 29.40 km; KBO	7 386BT122-41-40 78.0 59.60 CLEAR O F(50,50) 60 dBu = 64.99 km								
KICE LIC Sequoia Communications, 264C Bend OR BLH-5892 100.									
KARY-FM LIC Northwest Broadcast Repr 265A Grandview WA BMLH-910207KA 100.	6 46-14-03 59.6 116.5 15 9 -27 119-48-49 240.5 101.5 CLEAR								

>> End of channel 211C2 study <<

## FM Interference study

Title: THE DALLES, OR Channel 213C2 ( 90.5 MHz) ERP: .20 kW; EAH: 561 m Database: FCC 04/09/98  Latitude: 45-42-43 Longitude: 121-07-00 Safety zone: 80 km
Call Auth Licensee name Chan ERP-kW Latitude Br-to Dist. Req. City of License St FCC File no. Freq EAH-m Longitude -from (km) (km)
KOIN LIC KOIN-TV, INC. 6 100 45-30-58 260.8 127.9 140.5 PORTLAND OR 85.0 533 122-43-59 79.6 -12.6 SHORT Proposed F(50,10) 69.5 dBu = 17.29 km; KOIN F(50,50) 47 dBu = 123.2 km
KBPS-FM LIC       Benson Polytechnic Schoo *210C2 8.70       45-30-58 260.8 127.9 49.31         Portland       OR       89.9 293 122-43-59 79.6 78.64 CLEAR         Proposed F(50,50)       100 dBu = .978 km; KBPS-FM F(50,50) 60 dBu = 48.33 km         Proposed F(50,50)       60 dBu = 29.40 km; KBPS-FM F(50,50) 100 dBu = 4.704 km
KOLU       LIC       Riverview Baptist Christ *211C2 4.10       46-04-59       74.0 157.3 50.29         Pasco       WA       90.1 305 119-09-38 255.5 107.0 CLEAR         Proposed F(50,50)       80 dBu = 7.717 km; KOLU       F(50,50)       60 dBu = 42.58 km         Proposed F(50,50)       60 dBu = 29.40 km; KOLU       F(50,50)       80 dBu = 14.43 km
KNWY LIC Washington State Univers *212C3 1.90 46-31-57 26.9 102.5 81.38 Yakima WA 90.3 273 120-30-37 207.3 21.17 CLEAR Proposed F(50,10) 54 dBu = 45.89 km; KNWY F(50,50) 60 dBu = 34.67 km Proposed F(50,50) 60 dBu = 29.40 km; KNWY F(50,10) 54 dBu = 51.98 km
KZOE       LIC       Columbia Heights Christi *212A       .50       46-09-47 291.1 143.8 69.76         Longview       WA       90.3 239 122-51-14 109.8 74.00 CLEAR         Proposed F(50,10)       54 dBu = 45.89 km; KZOE       F(50,50) 60 dBu = 23.86 km         Proposed F(50,50)       60 dBu = 29.40 km; KZOE       F(50,10) 54 dBu = 35.89 km
NEW APC The Commun. Advisory Bd. *213A .40 44-04-41 185.4 182.4 106.6 Bend OR 90.5 177 121-19-57 5.3 75.78 CLEAR Proposed F(50,10) 40 dBu = 86.89 km; NEW F(50,50) 60 dBu = 19.70 km Proposed F(50,50) 60 dBu = 29.40 km; NEW F(50,10) 40 dBu = 60.84 km
NEW APC Pensacola Christian Coll *213C3 4.50 44-04-39 185.4 182.4 122.4 Bend OR 90.5 173 121-19-52 5.2 60.02 CLEAR Proposed F(50,10) 40 dBu = 86.89 km; NEW F(50,50) 60 dBu = 34.19 km Proposed F(50,50) 60 dBu = 29.40 km; NEW F(50,10) 40 dBu = 93.01 km
KBOO       LIC       The KBOO       Foundation       *214C1       26.5       45-29-20       259.1       125.6       124.5         Portland       OR       90.7       386BT122-41-40       78.0       1.036       CLOSE         Proposed F(50,10)       54 dBu = 45.89 km; KBOO       F(50,50)       60 dBu = 64.99 km         Proposed F(50,50)       60 dBu = 29.40 km; KBOO       F(50,10)       54 dBu = 95.14 km
KNWR LIC Washington State Univers *214C1 5 47-15-48 17.6 181.2 127.3 Ellensburg WA 90.7 777BT120-23-31 198.1 53.88 CLEAR Proposed F(50,10) 54 dBu = 45.89 km; KNWR F(50,50) 60 dBu = 66.51 km Proposed F(50,50) 60 dBu = 29.40 km; KNWR F(50,10) 54 dBu = 97.93 km
KRBM       LIC       Oregon       Public       Broadcasti       *215C2       25       45-35-21       94.0       165.7       57.16         Pendleton       OR       90.9       180BT118-59-53       275.5       108.6       CLEAR         Proposed F(50,50)       80 dBu = 7.717 km; KRBM       F(50,50)       60 dBu = 49.44 km         Proposed F(50,50)       60 dBu = 29.40 km; KRBM       F(50,10)       80 dBu = 18.33 km

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 66 May 5, 1998

## FM Interference study

Title: THE DALLES, OR Channel 213C2 ( 90.5 MHz) ERP: .20 kW; EAH: 561 m  Latitude: 45-42-43 Longitude: 121-07-00										
Call Auth Licensee name Chan ERP-kW City of License St FCC File no. Freq EAH-m										
KYPL       CP       Growing Christian Founda *216C2       10         Yakima       WA       91.1       290         Proposed F(50,50)       100 dBu = .978 km; KYPL       F         Proposed F(50,50)       60 dBu = 29.40 km; KYPL       F	120-24-05 212.0 54.46 CLEAR (50,50) 60 dBu = 49.41 km									
KUFOCPAmerican Radio Systems L266C22.5PortlandOR BPH-970219IH101.1395	45-30-57 260.7 127.8 35 122-43-52 79.6 92.80 CLEAR									
KGDN CP West Pasco Fine Arts Rad 267C3 2.75 Pasco WA BPH-970416IB 101.3 305	46-05-47 73.3 155.2 17 119-11-36 254.7 138.2 CLEAR									

>> End of channel 213C2 study <<

Latitude: 45-42-43

### McCLANATHAN & ASSOCIATES PORTLAND, OREGON

### FM Interference study

Title: THE DALLES, OR Longitude: 121-07-00 Channel 215C2 ( 90.9 MHz) ERP: .20 kW; EAH: 561 m Database: FCC 04/09/98 Safety zone: 80 km Chan ERP-kW Latitude Br-to Dist. Reg. Call Auth Licensee name City of License St FCC File no. Freq EAH-m Longitude -from (km) (km) LIC KOIN-TV, INC. 6 100 45-30-58 260.8 127.9 135.5 KOIN 533 122-43-59 79.6 -7.60 SHORT 85.0 PORTLAND OR Proposed F(50,10) 74 dBu = 12.33 km; KOINF(50,50) 47 dBu = 123.2 km 46-31-57 26.9 102.5 35.65 LIC Washington State Univers \*212C3 1.90 KNWY 120-30-37 207.3 66.89 CLEAR Yakima WA 90.3 273 F(50,50) 60 dBu = 34.67 km Proposed F(50,50) 100 dBu = .978 km; KNWYProposed F(50,50) 60 dBu = 29.40 km; KNWY F(50,50)100 dBu = 2.675 kmNEW APC The Commun. Advisory Bd. \*213A .40 44-04-41 185.4 182.4 35.51 Bend 177 121-19-57 5.3 146.9 CLEAR OR 90.5 Proposed F(50.50) 80 dBu = 7.717 km: NEW F(50,50)60 dBu = 19.70 km60 dBu = 29.40 km; NEW Proposed F(50,50) F(50,50)80 dBu = 6.114 kmKBOO LIC The KBOO Foundation \*214C1 26.5 45-29-20 259.1 125.6 124.5 Portland OR 90.7 386BT122-41-40 78.0 1.036 CLOSE Proposed F(50,10) 54 dBu = 45.89 km; KBOOF(50,50) 60 dBu = 64.99 km Proposed F(50,50) 60 dBu = 29.40 km; KBOO F(50,10)54 dBu = 95.14 kmKNWR LIC Washington State Univers \*214C1 47-15-48 17.6 181.2 127.3 Ellensburg WA 90.7 777BT120-23-31 198.1 53.88 CLEAR Proposed F(50,10) 54 dBu = 45.89 km; KNWR F(50,50) 60 dBu = 66.51 km Proposed F(50,50) 60 dBu = 29.40 km; KNWR F(50,10)54 dBu = 97.93 kmKRBM LIC Oregon Public Broadcasti \*215C2 45-35-21 94.0 165.7 155.7 25 Pendleton OR 90.9 180BT118-59-53 275.5 10.05 CLOSE Proposed F(50,10) 40 dBu = 86.89 km; KRBMF(50,50) 60 dBu = 49.44 km Proposed F(50,50)  $60^{\circ} dBu = 29.40 \text{ km}$ ; KRBM F(50,10)40 dBu = 126.3 kmKVTI LIC Clover Park Technical Co \*215C1 47-09-39 325.8 196.3 162.1 51 Tacoma 122-34-35 144.7 34.14 CLEAR WA 90.9 111 Proposed F(50,10) 40 dBu = 86.89 km; KVTIF(50,50) 60 dBu = 46.77 kmProposed F(50,50) 60 dBu = 29.40 km; KVTI 40 dBu = 132.7 kmF(50,10)KYPL CP Growing Christian Founda \*216C2 46-30-48 31.5 104.8 102.2 10 Yakima 120-24-05 212.0 2.603 CLOSE 290 WA 91.1 Proposed F(50,10) 54 dBu = 45.89 km; KYPLF(50,50)60 dBu = 49.41 kmProposed F(50,50) 60 dBu = 29.40 km; KYPL F(50,10)54 dBu = 72.84 kmLIC Centralia Community Coll \*217A KCED 46-42-56 308.8 181.0 32.58 1 Centralia -21 122-57-48 127.5 148.4 CLEAR WA 91.3 Proposed F(50,50) 80 dBu = 7.717 km; KCED F(50,50)60 dBu = 10.25 kmProposed F(50,50) 60 dBu = 29.40 km; KCED F(50,50)80 dBu = 3.179 kmKOPB-FM LIC Oregon Public Broadcasti \*218C 70 45-31-22 261.2 129.3 82.58 Portland 91.5 475 122-45-07 80.0 46.69 CLEAR OR 100 dBu = .978 km; KOPB-FM F(50,50) 60 dBu = 81.60 km Proposed F(50,50) 60 dBu = 29.40 km; KOPB-FM F(50,50) Proposed F(50,50) 100 dBu = 11.20 km

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 70 May 5, 1998

## FM Interference study

Title: THE DALLES, OR Latitude: 45-42-43 Channel 215C2 ( 90.9 MHz) ERP: .20 kW; EAH: 561 m Longitude: 121-07-00

	Licensee name nse St FCC File no.	Chan ERP-kW Freq EAH-m			Req.
PRM ADD The Dalles	LifeTalk Broadcasting As OR DOC-96-12	268C3 101.5	45-31-28 121-07-22		17 CLOSE
PRM ADD The Dalles	Common Ground Broadcasti OR DOC-96-12	268C3 101.5	45-34-00 120-55-00		17 CLOSE
KZXR LIC Prosser	Cormac C. Thompson WA BLH-901119KI		46-11-12 119-45-13	 	17 CLEAR

<sup>&</sup>gt;> End of channel 215C2 study <<

## EXHIBIT 3

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 1 May 5, 1998

Title: THE DALLES, OR

## Educational FM/TV Channel 6 Interference area

Interference Site Lat 45-	e -42-08	KOIN Channel 6 C/R 533 m AAT Latitude: 45-30-58 Longitude: 122-43-59						L		5 <b>81 m</b> d <b>e:</b> 4	AAT 45-42-	-43
Bear. (deg)	Dist (km)	Bear. (deg)	Dist (km)	Haat (m)	ERP (kW)	F.S. (dBu)	U/D (dB)	Bear. (deg)	Dist (km)	Haat (m)	ERP	F.S. (dBu)
.0	5.9	76.8	122	555	100	47.9	31.0*	306.4	8.21	502	.20	78.9
1.0	6.0	76.8	122	555	100	47.9	31.1*	307.1		498	.20	78.9
2.0	6.1	76.8	123	555	100	47.8	31.2*	308.0		494	.20	79.0
3.0	6.1	76.8	123	555	100	47.8	31.3*	308.9	8.07	494	.20	79.0
4.0	6.2	76.8	123	555	100	47.7	31.4*	309.7		489	.20	79.1
5.0	6.3	76.8	123	555	100	47.7	31.4*	310.5		485	.20	79.1
6.0 7.0	6.3	76.8	123	555	100	47.7	31.5*	311.3		481	.20	79.2
8.0	6.4 6.4	76.7 76.7	123	555	100	47.6	31.6*	312.1		477	.20	79.2
9.0	6.5	76.7	123 123	555 555	100	47.6	31.7*	313.0		473	.20	79.3
10.0	6.6	76.7	124	555	100 100	47.5 47.5	31.8*	314.0		473	.20	79.3
11.0	6.7	76.7	124	555	100	47.5	31.9* 32.0*	314.9		468	.20	79.4
12.0	6.7	76.7	124	555	100	47.4	32.0*	315.7 316.8		464	.20	79.4
13.0	6.8	76.7	124	555	100	47.3	32.2*	317.9		464 464	.20	79.5
14.0	6.9	76.6	124	555	100	47.3	32.4*	319.0		463	.20 .20	79.6 79.6
15.0	7.0	76.6	124	555	100	47.2	32.5*	320.2		463	.20	79.0
16.0	7.1	76.6	124	555	100	47.2	32.6*	321.3		463	.20	79.8
17.0	7.2	76.6	125	555	100	47.1	32.7*	322.4		462	.20	79.8
18.0	7.3	76.6	125	555	100	47.1	32.8*	323.6		462	.20	79.9
19.0	7.4	76.6	125	555	100	47.0	33.0*	324.8		462	.20	80.0
20.0	7.3	76.7	125	555	100	47.0	33.0*	324.6	7.09	462	.20	80.3
21.0 22.0	7.1	76.8	125	555	100	47.0	33.0*	323.8		462	.20	80.6
23.0	6.9 6.7	76.9	125	555	100	47.0	33.0*	323.1		462	.20	80.9
24.0	6.5	77.0 77.1	125 125	555	100	47.0	33.0*	322.2		462	.20	81.3
25.0	6.3	77.2	125	554 554	100	47.0	33.0*	320.8		463	.20	81.7
26.0	6.2	77.3	125	554	100 100	47.0 47.0	33.0*	319.9		463	.20	82.0
27.0	6.1	77.3	125	554	100	47.0	33.0* 33.0*	319.1		463	.20	82.3
28.0	5.9	77.4	125	554	100	47.0	33.0*	318.2 317.4		463	.20	82.7
29.0	5.8	77.5	125	554	100	47.0	33.0*	316.5		464 464	.20	83.0
30.0	5.7	77.6	125	554	100	47.0	33.0*	315.7		464	.20	83.3 83.6
31.0	5.6	77.6	125	554	100	47.0	33.0*	314.8		468	.20	83.9
32.0	5.5	77.7	125	554	100	47.0	33.0*	314.0		473	.20	84.1
33.0	5.4	77.8	125	554	100	47.0	33.0*	313.0		477	.20	84.4
34.0	5.3	77.8	125	554	100	47.0	33.0*	312.2		477	.20	84.6
35.0	5.2	77.9	125	554	100	47.0	33.0*	311.3		481	.20	84.9
36.0	5.1	77.9	125	554	100	47.0	33.0*	310.3	4.73	485	.20	85.1
37.0 38.0	5.0	78.0	125	554	100	47.0	33.0*	308.5		494	.20	85.3
39.0	4.9 4.8	78.1	125	554	100	47.0	33.0*	307.6		498	.20	85.5
40.0	4.8	78.1 78.2	125 125	554 554	100	47.0	33.0*	306.6		502	.20	85.7
41.0	4.7	78.2	125	554 554	100 100	47.0	33.0*	305.6		506	.20	85.9
42.0	4.6	78.3	125	554	100	47.0 47.0	33.0*	304.6		511	.20	86.1
43.0	4.6	78.3	125	554	100	47.0	33.0* 33.0*	303.7		515	.20	86.3
44.0	4.5	78.4	125	554	100	47.0	33.0*	302.7 301.7		519	.20	86.5
		- <del>-</del>			200		55.0.	301./	7.1U	523	.20	86.6

# McCLANATHAN & ASSOCIATES PORTLAND, OREGON

Page 2 May 5, 1998

Title: THE DALLES, OR

### Educational FM/TV Channel 6 Interference area

Interfer Site Lat 45- Lon 121-	42-08		R 5	33 m	TAA 2-08-5	58		La	R 5	581 m	AAT 5-42-	43
Bear. (deg)	Dist (km)	Bear. I	(km)	(m)	ERP (kW)	F.S. (dBu)	U/D (dB)	Bear. (deg)	(km)	Haat (m)	ERP (kW)	F.S. (dBu)
45.0	4.4	78.4	125	554	100	47.0	33.0*	300.7	4.04	527	.20	86.8
46.0	4.4	78.4	125	554	100	47.0	33.0*	299.7		532	.20	86.9
47.0	4.3	78.5	125	554	100	47.0	33.0*	298.7		536	.20	87.1
48.0	4.3	78.5	125	554	100	47.0	33.0*	297.6		540	.20	87.2
49.0	4.2	78.6	125	554	100	47.0	33.0*	296.7		544	.20	87.4
50.0	4.2	78.6	125	554	100	47.0	33.0*	295.6			.20	87.5
51.0	4.2	78.6	125	554	100	47.0	33.0*	294.5		553	.20	87.7
52.0	4.1	78.7	125	554	100	47.0	33.0*				.20	87.8
53.0 54.0	4.1 4.1	78.7 78.8	125 125	554 554	100 100	47.0 47.0	33.0* 33.0*			561 565	.20 .20	87.9
55.0	4.1	78.8	125	554 554	100	47.0	33.0*	291.4			.20	88.0 88.1
56.0	4.0	78.8	125	554	100	47.0	33.0*	289.2			.20	88.3
57.0	4.0	78.9	125	554	100	47.0	33.0*	288.2			.20	88.4
58.0	3.9	78.9	125	554	100	47.0	33.0*	287.0			.20	88.5
59.0	3.9	78.9	125	554	100	47.0	33.0*	285.9			.20	88.6
60.0	3.9	79.0	125	554	100	47.0	33.0*	284.8			.20	88.6
61.0	3.8	79.0	125	554	100	47.0	33.0*	283.7			.20	88.7
62.0	3.8	79.0	125	553	100	47.0	33.0*	282.0	3.36	607	.20	88.7
63.0	3.8	79.1	125	553	100	47.0	33.0*	280.9	3.34	612	.20	88.8
64.0	3.7	79.1	125	553	100	47.0	33.0*	279.8			.20	88.8
65.0	3.7	79.1	125	553	100	47.0	33.0*	278.7			.20	88.9
66.0	3.7	79.2	125	553	100	47.0	33.0*	277.6			.20	89.0
67.0	3.7	79.2	125	553	100	47.0	33.0*	276.4			.20	89.0
68.0	3.7	79.2	125	553	100	47.0	33.0*	275.3			.20	89.1
69.0	3.7	79.3	125	553	100	47.0	33.0*	274.2			.20	89.1
70.0	3.6	79.3	125	553	100	47.0	33.0*	273.1			.20	89.2
71.0	3.6	79.3	125	553	100	47.0	33.0*	272.0			.20	89.2
72.0	3.6	79.3	125	553 553	100	47.0 47.0	33.0*	270.8				89.3
73.0 74.0	3.6 3.6	79.4 79.4	125 125	553	100 100	47.0	33.0* 33.0*		3.16 3.16			89.3 89.3
75.0	3.6	79.4	125	553	100		33.0*		3.15			89.3
76.0	3.6	79.5	125	553	100	47.0	33.0*		3.14		.20	89.4
77.0	3.6	79.5	125	553	100	47.0	33.0*		3.14			89.4
78.0	3.6	79.5	125	553	100	47.0	33.0*		3.13			
79.0	3.6	79.5	125	553	100	47.0	33.0*		3.13			
80.0	3.6	79.6	125	553	100	47.0	33.0*		3.12			
81.0	3.6	79.6	125	553	100	47.0	33.0*		3.13			
82.0	3.6	79.6	125	553	100	47.0	33.0*	259.4	3.12	665	.20	
83.0	3.6	79.7	125	553	100	47.0	33.0*		3.13			
84.0	3.6	79.7	125	553	100	47.0	33.0*		3.14			
85.0	3.6	79.7	125	553	100	47.0	33.0*		3.14			
86.0	3.6	79.7	125		100		33.0*		3.14			
87.0	3.6	79.8	125		100		33.0*		7 3.15			
88.0	3.6	79.8	125		100		33.0*		5 3.17			
89.0	3.6	79.8	125	553	100	47.0	33.0*	251.4	3.17	7 673	.20	89.3

Page 3 May 5, 1998

Title: THE DALLES, OR

## Educational FM/TV Channel 6 Interference area

Carrell   Carr	Interfer Site Lat 45- Lon 121-	42-08		R 5 titud	33 m	AAT 5-30-	58		La La	/R 5 atitud	81 m	AAT 5-42-	43
90.0         3.6         79.9         125         553         100         47.0         33.0*         250.3         3.18         674         .20         89.9           91.0         3.6         79.9         125         553         100         47.0         33.0*         248.1         3.21         676         .20         89.9           93.0         3.7         80.0         125         553         100         47.0         33.0*         246.9         3.22         678         .20         89.9           94.0         3.7         80.0         125         553         100         47.0         33.0*         246.9         3.22         678         .20         89.9           95.0         3.6         80.0         125         552         100         47.0         33.0*         245.8         3.24         679         .20         88.9           96.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.9           99.0         3.7         80.1         125         552         100         47.0         33.0*         238.7         3.41 <td< th=""><th></th><th></th><th>(deg)</th><th>(km)</th><th>(m)</th><th>(kW)</th><th>(dBu)</th><th>(dB)</th><th>(deg)</th><th>(km)</th><th>(m)</th><th>(kW)</th><th>F.S. (dBu)</th></td<>			(deg)	(km)	(m)	(kW)	(dBu)	(dB)	(deg)	(km)	(m)	(kW)	F.S. (dBu)
92.0         3.6         79.9         125         553         100         47.0         33.0*         248.1         3.22         678         20         89.9           93.0         3.7         80.0         125         553         100         47.0         33.0*         246.9         3.22         678         20         89.9           95.0         3.6         80.0         125         552         100         47.0         33.0*         245.1         3.30         679         20         88.           96.0         3.7         80.1         125         552         100         47.0         33.0*         244.0         3.32         680         20         88.           97.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         20         88.           99.0         3.7         80.1         125         552         100         47.0         33.0*         239.7         3.41         685         20         88.           100.0         3.8         80.2         125         552         100         47.0         33.0*         239.7         3.41         686	90.0	3.6	79.9	125	553	100	47.0	33.0*	250.3	3.18	674	.20	89.3
93.0         3.7         80.0         125         553         100         47.0         33.0*         246.9         3.22         678         .20         89.9           94.0         3.7         80.0         125         552         100         47.0         33.0*         245.8         3.24         679         .20         88.           95.0         3.6         80.0         125         552         100         47.0         33.0*         244.0         3.32         680         .20         88.           97.0         3.7         80.1         125         552         100         47.0         33.0*         244.0         3.34         682         .20         88.           98.0         3.7         80.1         125         552         100         47.0         33.0*         240.8         3.38         684         .20         88.           100.0         3.7         80.1         125         552         100         47.0         33.0*         238.7         3.41         686         .20         88.           101.0         3.8         80.2         125         552         100         47.0         33.0*         236.6         3.49         68													89.2
94.0         3.7         80.0         125         553         100         47.0         33.0*         245.8         3.24         679         .20         88.9           96.0         3.7         80.0         125         552         100         47.0         33.0*         244.0         3.32         680         .20         88.           97.0         3.7         80.1         125         552         100         47.0         33.0*         244.0         3.34         682         .20         88.           98.0         3.7         80.1         125         552         100         47.0         33.0*         241.0         3.34         682         .20         88.           99.0         3.7         80.1         125         552         100         47.0         33.0*         241.0         3.38         684         .20         88.           100.0         3.7         80.2         125         552         100         47.0         33.0*         238.7         3.41         686         .20         88.           101.0         3.8         80.3         125         552         100         47.0         33.0*         236.6         3.49         89													89.2
95.0         3.6         80.0         125         552         100         47.0         33.0*         245.1         3.30         679         .20         88.997.0         3.7         80.1         125         552         100         47.0         33.0*         244.0         3.34         682         .20         88.99.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.99.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         684         .20         88.100.0         3.7         80.1         125         552         100         47.0         33.0*         240.8         3.36         684         .20         88.100.0         3.7         80.2         125         552         100         47.0         33.0*         238.7         3.44         686         .20         88.103.0         3.8         80.2         125         552         100         47.0         33.0*         237.6         3.49         689         .20         88.1           104.0         3.8         80.3         125         552         100         47.0													89.2
96.0         3.7         80.0         125         552         100         47.0         33.0*         244.0         3.32         680         .20         88.           98.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.           99.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.38         684         .20         88.           100.0         3.8         80.2         125         552         100         47.0         33.0*         239.7         3.41         686         .20         88.           102.0         3.8         80.2         125         552         100         47.0         33.0*         237.6         3.46         688         .20         88.           103.0         3.8         80.3         125         552         100         47.0         33.0*         236.6         3.49         689         .20         88.           105.0         3.9         80.3         125         552         100         47.0         33.0*         231.2         3.66         6													89.1
97.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.           99.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.           100.0         3.7         80.2         125         552         100         47.0         33.0*         239.7         3.41         685         .20         88.           101.0         3.8         80.2         125         552         100         47.0         33.0*         238.7         3.46         686         .20         88.           102.0         3.8         80.3         125         552         100         47.0         33.0*         236.6         3.49         689         .20         88.           103.0         3.8         80.3         125         552         100         47.0         33.0*         235.5         3.52         690         .20         88.           105.0         3.9         80.4         125         552         100         47.0         33.0*         234.4         3.56													
98.0         3.7         80.1         125         552         100         47.0         33.0*         241.9         3.36         683         .20         88.           100.0         3.7         80.2         125         552         100         47.0         33.0*         240.8         3.38         684         .20         88.           101.0         3.8         80.2         125         552         100         47.0         33.0*         238.7         3.44         686         .20         88.           102.0         3.8         80.2         125         552         100         47.0         33.0*         237.6         3.46         688         .20         88.           103.0         3.8         80.3         125         552         100         47.0         33.0*         235.5         3.52         690         .20         88.           104.0         3.8         80.3         125         552         100         47.0         33.0*         234.4         3.56         691         .20         88.           105.0         3.9         80.4         125         552         100         47.0         33.0*         231.2         3.66 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>													
99.0 3.7 80.1 125 552 100 47.0 33.0* 240.8 3.38 684 .20 88. 100.0 3.7 80.2 125 552 100 47.0 33.0* 239.7 3.41 685 .20 88. 101.0 3.8 80.2 125 552 100 47.0 33.0* 238.7 3.44 686 .20 88. 102.0 3.8 80.2 125 552 100 47.0 33.0* 237.6 3.46 688 .20 88. 103.0 3.8 80.3 125 552 100 47.0 33.0* 237.6 3.46 688 .20 88. 103.0 3.8 80.3 125 552 100 47.0 33.0* 235.5 3.52 690 .20 88. 105.0 3.9 80.3 125 552 100 47.0 33.0* 236.6 3.49 689 .20 88. 105.0 3.9 80.4 125 552 100 47.0 33.0* 235.5 3.52 690 .20 88. 106.0 3.9 80.4 125 552 100 47.0 33.0* 233.3 3.59 692 .20 88. 107.0 3.9 80.4 125 552 100 47.0 33.0* 233.3 3.59 692 .20 88. 108.0 4.0 80.4 125 552 100 47.0 33.0* 233.2 3.62 693 .20 88. 109.0 4.0 80.5 125 552 100 47.0 33.0* 231.2 3.66 694 .20 88. 110.0 4.0 80.5 125 552 100 47.0 33.0* 231.2 3.66 694 .20 88. 111.0 4.1 80.6 125 552 100 47.0 33.0* 230.1 3.70 695 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 229.2 3.75 696 .20 87. 111.0 4.2 80.7 125 552 100 47.0 33.0* 226.1 3.88 699 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 226.1 3.88 699 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 226.1 3.88 699 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 225.0 3.93 700 .20 87. 111.0 4.1 80.6 125 552 100 47.0 33.0* 225.0 3.93 700 .20 87. 111.0 4.6 81.0 125 552 100 47.0 33.0* 225.0 3.93 700 .20 87. 111.0 4.6 81.0 125 552 100 47.0 33.0* 211.1 4.16 706 .20 86. 111.0 4.6 81.0 125 552 100 47.0 33.0* 211.1 4.16 706 .20 86. 112.0 4.6 81.0 125 552 100 47.0 33.0* 211.3 4.84 720 .20 86. 112.0 4.6 81.0 125 552 100 47.0 33													
100.0   3.7   80.2   125   552   100   47.0   33.0*   239.7   3.41   685   .20   88.     101.0   3.8   80.2   125   552   100   47.0   33.0*   238.7   3.44   686   .20   88.     102.0   3.8   80.2   125   552   100   47.0   33.0*   237.6   3.46   688   .20   88.     103.0   3.8   80.3   125   552   100   47.0   33.0*   236.6   3.49   689   .20   88.     104.0   3.8   80.3   125   552   100   47.0   33.0*   236.6   3.49   689   .20   88.     105.0   3.9   80.3   125   552   100   47.0   33.0*   235.5   3.52   690   .20   88.     106.0   3.9   80.4   125   552   100   47.0   33.0*   233.3   3.59   692   .20   88.     107.0   3.9   80.4   125   552   100   47.0   33.0*   232.2   3.62   693   .20   88.     108.0   4.0   80.4   125   552   100   47.0   33.0*   232.2   3.62   693   .20   88.     109.0   4.0   80.5   125   552   100   47.0   33.0*   232.2   3.66   694   .20   88.     111.0   4.0   80.5   125   552   100   47.0   33.0*   231.2   3.66   694   .20   88.     112.0   4.1   80.5   125   552   100   47.0   33.0*   230.1   3.70   695   .20   87.     113.0   4.2   80.6   125   552   100   47.0   33.0*   229.2   3.75   696   .20   87.     114.0   4.2   80.6   125   552   100   47.0   33.0*   229.2   3.75   696   .20   87.     115.0   4.2   80.6   125   552   100   47.0   33.0*   229.2   3.75   696   .20   87.     116.0   4.3   80.7   125   552   100   47.0   33.0*   225.0   3.93   700   .20   87.     117.0   4.3   80.8   125   552   100   47.0   33.0*   225.0   3.93   700   .20   87.     117.0   4.5   80.9   125   552   100   47.0   33.0*   222.0   4.04   703   .20   87.     118.0   4.4   80.8   125   552   100   47.0   33.0*   222.0   4.04   703   .20   87.     117.0   4.5   80.9   125   552   100   47.0   33.0*   222.0   4.04   703   .20   87.     120.0   4.5   80.9   125   552   100   47.0   33.0*   221.1   4.16   706   .20   86.     121.0   4.6   81.0   125   552   100   47.0   33.0*   211.4   4.6   711   .20   86.     122.0   4.6   81.0   125   552   100   47.0   33.0*   217.3   4.43   713   .20   86.													
101.0													88.6
102.0       3.8       80.2       125       552       100       47.0       33.0*       237.6       3.46       688       .20       88         103.0       3.8       80.3       125       552       100       47.0       33.0*       236.6       3.49       689       .20       88         104.0       3.8       80.3       125       552       100       47.0       33.0*       235.5       3.52       690       .20       88         105.0       3.9       80.4       125       552       100       47.0       33.0*       233.3       3.59       692       .20       88         106.0       3.9       80.4       125       552       100       47.0       33.0*       233.2       3.62       693       .20       88         107.0       3.9       80.4       125       552       100       47.0       33.0*       232.2       3.66       694       .20       88         108.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87         110.0       4.0       80.5       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>88.6</td></td<>													88.6
103.0       3.8       80.3       125       552       100       47.0       33.0*       236.6       3.49       689       .20       88         104.0       3.8       80.3       125       552       100       47.0       33.0*       235.5       3.52       690       .20       88         105.0       3.9       80.4       125       552       100       47.0       33.0*       234.4       3.56       691       .20       88         106.0       3.9       80.4       125       552       100       47.0       33.0*       232.2       3.62       693       .20       88         107.0       3.9       80.4       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88         108.0       4.0       80.5       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88         109.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.76       696       .20       87         111.0       4.1       80.6       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>88.5</td></td<>													88.5
104.0       3.8       80.3       125       552       100       47.0       33.0*       235.5       3.52       690       .20       88         105.0       3.9       80.3       125       552       100       47.0       33.0*       234.4       3.56       691       .20       88         106.0       3.9       80.4       125       552       100       47.0       33.0*       233.2       3.62       693       .20       88         108.0       4.0       80.4       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88         109.0       4.0       80.5       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88         110.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87         111.0       4.1       80.5       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87         112.0       4.1       80.6       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>88.4</td></td<>													88.4
106.0       3.9       80.4       125       552       100       47.0       33.0*       233.3       3.59       692       .20       88.107.0         107.0       3.9       80.4       125       552       100       47.0       33.0*       232.2       3.62       693       .20       88.108.0         109.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87.110.0         110.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87.111.0         111.0       4.1       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0         112.0       4.1       80.6       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87.112.0         113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.113.0         115.0       4.2       80.7						100		33.0*					88.3
107.0       3.9       80.4       125       552       100       47.0       33.0*       232.2       3.62       693       .20       88.108.0       4.0       80.4       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88.109.0       88.109.0       47.0       33.0*       230.1       3.70       695       .20       87.110.0       4.0       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0       4.1       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0       4.1       80.6       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.111.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.111.0       4.2       80.7       125       552       100       47.0       33.0*       224.1 <td>105.0</td> <td>3.9</td> <td>80.3</td> <td>125</td> <td>552</td> <td>100</td> <td>47.0</td> <td>33.0*</td> <td>234.4</td> <td>3.56</td> <td>691</td> <td>.20</td> <td>88.3</td>	105.0	3.9	80.3	125	552	100	47.0	33.0*	234.4	3.56	691	.20	88.3
108.0       4.0       80.4       125       552       100       47.0       33.0*       231.2       3.66       694       .20       88.         109.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87.         110.0       4.0       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.         111.0       4.1       80.5       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87.         112.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.         113.0       4.2       80.6       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.         114.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.         115.0       4.2       80.7       125       552													88.2
109.0       4.0       80.5       125       552       100       47.0       33.0*       230.1       3.70       695       .20       87.110.0         110.0       4.0       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0         111.0       4.1       80.6       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87.112.0         112.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.113.0       4.2       80.7       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       86.115.0       87.115.0       87.115.0       87.115.0       87.115.0       87.115.0       87.115.0       87.115.0       87.115.0       87													88.1
110.0       4.0       80.5       125       552       100       47.0       33.0*       229.2       3.75       696       .20       87.111.0         111.0       4.1       80.5       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87.112.0         112.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.113.0         113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.114.0         114.0       4.2       80.7       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.115.0         115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.116.0         116.0       4.3       80.7       125       552       100       47.0       33.0*       222.0       4.04       703       .20       87.117.0       4.3       80.8       125       552       <													88.0
111.0       4.1       80.5       125       552       100       47.0       33.0*       228.2       3.79       697       .20       87.112.0         112.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.113.0         113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.114.0         114.0       4.2       80.7       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.115.0         115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.116.0         116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2       4.04       703       .20       87.117.0         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       1													87.9
112.0       4.1       80.6       125       552       100       47.0       33.0*       227.2       3.84       698       .20       87.13.0         113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.114.0         114.0       4.2       80.7       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.115.0         115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.116.0         116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2       4.04       703       .20       87.117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100													87.8
113.0       4.2       80.6       125       552       100       47.0       33.0*       226.1       3.88       699       .20       87.1         114.0       4.2       80.7       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.1         115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.1         116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2       4.04       703       .20       87.1         117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552													87.7
114.0       4.2       80.7       125       552       100       47.0       33.0*       225.0       3.93       700       .20       87.115.0         115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87.116.0         116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2       4.04       703       .20       87.117.0         117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125													
115.0       4.2       80.7       125       552       100       47.0       33.0*       224.1       3.98       701       .20       87         116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2       4.04       703       .20       87         117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         122.0       4.6       81.0       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>87.3</td></td<>													87.3
116.0       4.3       80.7       125       552       100       47.0       33.0*       223.2 4.04       703       .20       87         117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100													87.2
117.0       4.3       80.8       125       552       100       47.0       33.0*       222.0       4.10       705       .20       86         118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>87.1</td></td<>													87.1
118.0       4.4       80.8       125       552       100       47.0       33.0*       221.1       4.16       706       .20       86         119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>86.9</td></td<>													86.9
119.0       4.5       80.9       125       552       100       47.0       33.0*       220.1       4.22       708       .20       86         120.0       4.5       80.9       125       552       100       47.0       33.0*       219.2       4.29       710       .20       86         121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552       100       47.0       33.0*       215.1       4.67       716       .20       85         126.0       4.9       81.2       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>86.8</td></td<>													86.8
121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552       100       47.0       33.0*       215.1       4.67       716       .20       85         126.0       4.9       81.2       125       552       100       47.0       33.0*       214.2       4.75       718       .20       85         127.0       5.0       81.2       125       552       100       47.0       33.0*       213.3       4.84       720       .20       85         128.0       5.0       81.3       125       552 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>86.6</td></td<>													86.6
121.0       4.6       81.0       125       552       100       47.0       33.0*       218.1       4.36       711       .20       86         122.0       4.6       81.0       125       552       100       47.0       33.0*       217.3       4.43       713       .20       86         123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552       100       47.0       33.0*       215.1       4.67       716       .20       85         126.0       4.9       81.2       125       552       100       47.0       33.0*       214.2       4.75       718       .20       85         127.0       5.0       81.2       125       552       100       47.0       33.0*       213.3       4.84       720       .20       85         128.0       5.0       81.3       125       552 <td< td=""><td>120.0</td><td>4.5</td><td>80.9</td><td>125</td><td>552</td><td>100</td><td>47.0</td><td>33.0*</td><td>219.2</td><td>4.29</td><td>710</td><td>.20</td><td>86.5</td></td<>	120.0	4.5	80.9	125	552	100	47.0	33.0*	219.2	4.29	710	.20	86.5
123.0       4.6       81.0       125       552       100       47.0       33.0*       217.1       4.51       713       .20       86         124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552       100       47.0       33.0*       215.1       4.67       716       .20       85         126.0       4.9       81.2       125       552       100       47.0       33.0*       214.2       4.75       718       .20       85         127.0       5.0       81.2       125       552       100       47.0       33.0*       213.3       4.84       720       .20       85         128.0       5.0       81.3       125       552       100       47.0       33.0*       212.4       4.94       721       .20       85         129.0       5.1       81.4       125       552       100       47.0       33.0*       212.4       4.94       721       .20       85		4.6	81.0	125	552	100	47.0	33.0*	218.1	4.36	711	.20	86.4
124.0       4.7       81.1       125       552       100       47.0       33.0*       216.2       4.58       715       .20       85         125.0       4.8       81.1       125       552       100       47.0       33.0*       215.1       4.67       716       .20       85         126.0       4.9       81.2       125       552       100       47.0       33.0*       214.2       4.75       718       .20       85         127.0       5.0       81.2       125       552       100       47.0       33.0*       213.3       4.84       720       .20       85         128.0       5.0       81.3       125       552       100       47.0       33.0*       212.4       4.94       721       .20       85         129.0       5.1       81.4       125       552       100       47.0       33.0*       211.4       5.04       723       .20       85													86.2
125.0     4.8     81.1     125     552     100     47.0     33.0*     215.1     4.67     716     .20     85       126.0     4.9     81.2     125     552     100     47.0     33.0*     214.2     4.75     718     .20     85       127.0     5.0     81.2     125     552     100     47.0     33.0*     213.3     4.84     720     .20     85       128.0     5.0     81.3     125     552     100     47.0     33.0*     212.4     4.94     721     .20     85       129.0     5.1     81.4     125     552     100     47.0     33.0*     211.4     5.04     723     .20     85													86.0
126.0     4.9     81.2     125     552     100     47.0     33.0*     214.2     4.75     718     .20     85       127.0     5.0     81.2     125     552     100     47.0     33.0*     213.3     4.84     720     .20     85       128.0     5.0     81.3     125     552     100     47.0     33.0*     212.4     4.94     721     .20     85       129.0     5.1     81.4     125     552     100     47.0     33.0*     211.4     5.04     723     .20     85													85.9
127.0     5.0     81.2     125     552     100     47.0     33.0*     213.3     4.84     720     .20     85       128.0     5.0     81.3     125     552     100     47.0     33.0*     212.4     4.94     721     .20     85       129.0     5.1     81.4     125     552     100     47.0     33.0*     211.4     5.04     723     .20     85													85.7
128.0 5.0 81.3 125 552 100 47.0 33.0* 212.4 4.94 721 .20 85 129.0 5.1 81.4 125 552 100 47.0 33.0* 211.4 5.04 723 .20 85													85.6
129.0 5.1 81.4 125 552 100 47.0 33.0* 211.4 5.04 723 .20 85													85.4
													85.2
	130.0	5.2	81.4	125	552 552	100	47.0	33.0*					